

# ZQV 1.5N/3 BL



## General ordering data

Version	Cross-connector (terminal), Plugged, Number of poles: 3, Pitch in mm (P): 3.50, Insulated: Yes, 17.5 A, blue
Order No.	1985550000
Type	ZQV 1.5N/3 BL
GTIN (EAN)	4050118370485
Qty.	60 pc(s).

## Dimensions and weights

Depth	2.8 mm
Depth (inches)	0.11 inch
Height	21.9 mm
Height (inches)	0.862 inch
Width	9 mm
Width (inches)	0.354 inch
Net weight	0.888 g

## Temperatures

Storage temperature	-25 °C...55 °C
---------------------	----------------

## Material data

Material	Wemid
Colour	blue
UL 94 flammability rating	V-0

## Additional technical data

Explosion-tested version	Yes
Type of fixing	Plugged

## Cross-connector

Rated current, 2-pole	17.5 A
Rated current, multi-pole	17.5 A

## Dimensions

Pitch in mm (P)	3.5 mm
-----------------	--------

## General

Number of poles	3
-----------------	---

## Rating data

Rated current	17.5 A
---------------	--------

## Important note

Product information	<p>Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used</p>
---------------------	--

## Downloads

Approval/Certificate/Document of Conformity	<a href="#"><u>Confirmation of Standards EN 45545- 2_2020-10</u></a>
Engineering Data	<a href="#"><u>CAD data -- STEP</u></a>
Engineering Data	<a href="#"><u>Zuken E3.S</u></a>
Eplan Data Portal	<a href="#"><u>Eplan data</u></a>
CADENAS eCATALOG	<a href="#"><u>CAX data</u></a>
WSCAD Universe	<a href="#"><u>WSCAD data</u></a>
User Documentation	<a href="#"><u>2434520000_BED- ANL.ZQV_A_REIHE.pdf</u></a> <a href="#"><u>StorageConditionsTerminalBlocks</u></a> <a href="#"><u>User Manual ZQV 2.5</u></a>
Catalogues	<a href="#"><u>Catalogues in PDF-format</u></a>

## Classifications

ETIM 6.0	EC000489
ETIM 7.0	EC000489
ETIM 8.0	EC000489
ETIM 9.0	EC000489

ECLASS 9.0	27-14-11-40
ECLASS 9.1	27-14-11-40
ECLASS 10.0	27-14-11-40
ECLASS 11.0	27-14-11-40
ECLASS 12.0	27-14-11-40
ECLASS 13.0	27-25-03-03

### Approvals

ROHS	Conform
------	---------

### Related products:



Order No.: 1985580000  
Type: ZQV 1.5N/10

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
10, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985680000  
Type: ZQV 1.5N/10 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
10, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985800000  
Type: ZQV 1.5N/10 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
10, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985410000  
Type: ZQV 1.5N/2

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 2,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange

[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985530000  
Type: ZQV 1.5N/2 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 2,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985650000  
Type: ZQV 1.5N/2 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 2,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985600000  
Type: ZQV 1.5N/20

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
20, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985700000  
Type: ZQV 1.5N/20 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
20, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985810000  
Type: ZQV 1.5N/20 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
20, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985480000  
Type: ZQV 1.5N/3

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 3,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985670000  
Type: ZQV 1.5N/3 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 3,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985490000  
Type: ZQV 1.5N/4

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 4,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985570000  
Type: ZQV 1.5N/4 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 4,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985690000  
Type: ZQV 1.5N/4 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 4,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985500000  
Type: ZQV 1.5N/5

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 5,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985590000  
Type: ZQV 1.5N/5 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 5,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985710000  
Type: ZQV 1.5N/5 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 5,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985620000  
Type: ZQV 1.5N/50

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
50, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985720000  
Type: ZQV 1.5N/50 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
50, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985820000  
Type: ZQV 1.5N/50 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles:  
50, Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985510000  
Type: ZQV 1.5N/6

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 6,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985610000  
Type: ZQV 1.5N/6 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 6,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985730000  
Type: ZQV 1.5N/6 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 6,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985520000  
Type: ZQV 1.5N/7

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 7,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985630000  
Type: ZQV 1.5N/7 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 7,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985750000  
Type: ZQV 1.5N/7 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 7,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985540000  
Type: ZQV 1.5N/8

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 8,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985640000  
Type: ZQV 1.5N/8 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 8,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985770000  
Type: ZQV 1.5N/8 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 8,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985560000  
Type: ZQV 1.5N/9

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 9,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, orange  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985660000  
Type: ZQV 1.5N/9 BL

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 9,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, blue  
[PDF data sheet](#)  
[Add to Inquiry List](#)



Order No.: 1985790000  
Type: ZQV 1.5N/9 RD

Version:  
Cross-connector  
(terminal), Plugged,  
Number of poles: 9,  
Pitch in mm (P):  
3.50, Insulated: Yes,  
17.5 A, red  
[PDF data sheet](#)  
[Add to Inquiry List](#)