

ZQV 1.5N/3 RD



General ordering data

Version	Cross-connector (terminal), Plugged, Number of poles: 3, Pitch in mm (P): 3.50, Insulated: Yes, 17.5 A, red
Order No.	1985670000
Type	ZQV 1.5N/3 RD
GTIN (EAN)	4050118370348
Qty.	60 pc(s).

Dimensions and weights

Depth	2.8 mm
Depth (inches)	0.11 inch
Height	21.9 mm
Height (inches)	0.862 inch
Width	9 mm
Width (inches)	0.354 inch
Net weight	0.89 g

Temperatures

Storage temperature	-25 °C...55 °C
---------------------	----------------

Material data

Material	Wemid
Colour	red
UL 94 flammability rating	V-0

Additional technical data

Explosion-tested version	Yes
Type of fixing	Plugged

Cross-connector

Rated current, 2-pole	17.5 A
Rated current, multi-pole	17.5 A

Dimensions

Pitch in mm (P)	3.5 mm
-----------------	--------

General

Number of poles	3
-----------------	---

Rating data

Rated current	17.5 A
---------------	--------

Important note

Product information	<p>Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used</p>
---------------------	--

Downloads

Approval/Certificate/Document of Conformity	<u>Confirmation of Standards EN 45545- 2_2020-10</u>
Engineering Data	<u>CAD data -- STEP</u>
Engineering Data	<u>Zuken E3.S</u>
Eplan Data Portal	<u>Eplan data</u>
CADENAS eCATALOG	<u>CAX data</u>
WSCAD Universe	<u>WSCAD data</u>
User Documentation	<u>2434520000_BED- ANL.ZQV_A_REIHE.pdf</u> <u>StorageConditionsTerminalBlocks</u> <u>User Manual ZQV 2.5</u>
Catalogues	<u>Catalogues in PDF-format</u>

Classifications

ETIM 6.0	EC000489
ETIM 7.0	EC000489
ETIM 8.0	EC000489
ETIM 9.0	EC000489

ECLASS 9.0	27-14-11-40
ECLASS 9.1	27-14-11-40
ECLASS 10.0	27-14-11-40
ECLASS 11.0	27-14-11-40
ECLASS 12.0	27-14-11-40
ECLASS 13.0	27-25-03-03

Approvals

ROHS	Conform
------	---------

Related products:



Order No.: 1985580000
Type: ZQV 1.5N/10

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
10, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985680000
Type: ZQV 1.5N/10 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
10, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985800000
Type: ZQV 1.5N/10 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
10, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985410000
Type: ZQV 1.5N/2

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 2,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange

[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985530000
Type: ZQV 1.5N/2 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 2,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985650000
Type: ZQV 1.5N/2 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 2,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985600000
Type: ZQV 1.5N/20

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
20, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985700000
Type: ZQV 1.5N/20 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
20, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985810000
Type: ZQV 1.5N/20 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
20, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985480000
Type: ZQV 1.5N/3

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 3,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985550000
Type: ZQV 1.5N/3 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 3,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985490000
Type: ZQV 1.5N/4

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 4,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985570000
Type: ZQV 1.5N/4 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 4,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985690000
Type: ZQV 1.5N/4 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 4,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985500000
Type: ZQV 1.5N/5

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 5,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985590000
Type: ZQV 1.5N/5 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 5,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985710000
Type: ZQV 1.5N/5 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 5,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985620000
Type: ZQV 1.5N/50

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
50, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985720000
Type: ZQV 1.5N/50 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
50, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985820000
Type: ZQV 1.5N/50 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles:
50, Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985510000
Type: ZQV 1.5N/6

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 6,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985610000
Type: ZQV 1.5N/6 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 6,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985730000
Type: ZQV 1.5N/6 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 6,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985520000
Type: ZQV 1.5N/7

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 7,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985630000
Type: ZQV 1.5N/7 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 7,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985750000
Type: ZQV 1.5N/7 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 7,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985540000
Type: ZQV 1.5N/8

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 8,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985640000
Type: ZQV 1.5N/8 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 8,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985770000
Type: ZQV 1.5N/8 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 8,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985560000
Type: ZQV 1.5N/9

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 9,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, orange
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985660000
Type: ZQV 1.5N/9 BL

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 9,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, blue
[PDF data sheet](#)
[Add to Inquiry List](#)



Order No.: 1985790000
Type: ZQV 1.5N/9 RD

Version:
Cross-connector
(terminal), Plugged,
Number of poles: 9,
Pitch in mm (P):
3.50, Insulated: Yes,
17.5 A, red
[PDF data sheet](#)
[Add to Inquiry List](#)