



UT-L01 Tweezers test leads

- Length: 450mm, Probe length: 5mm
- Safety level: CAT III 1000V
- Application: SMT components measurement, universal test leads
- Amount: 1pc



UT-L02 BNC alligator clip test leads

- Length: 1000mm, Clip opening: 3mm
- Safety level: CAT II 600V 2A
- Application: BNC connector for instrument inputs
- Amount: 1pc



UT-L06 Dual head connectors

- Length: test leads 1200mm
- Safety level: CAT III 1000V 10A
- Application: Multifunctional connectors, all multimeters and clamps
- Amount: 1 pair



UT-L07 Probes

- Length: 1000mm, Probe length: 5mm+12mm
- Temperature condition: -15°C~40°C
- Safety level: CAT III 1000V 10A
- Features and application: Double insulated, lantern probes, removable probe protector, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L09 Dual head connectors

- Length: 1000mm, one head is 180°, the other is 90°
- Temperature condition: -15°C~40°C
- Safety level: CAT III 1000V 10A
- Features and application: Double insulated, banana plug with security mask and standard diameter, suitable for multiple devices, all multimeters and clamps
- Amount: 1 pair



UT-L10 Dual head multifunctional connectors

- Length: 1000mm, ϕ 4mm
- Temperature condition: -15°C~40°C
- Safety level: CAT III 1000V 10A
- Features and application: Banana plug, used for testing adapter cables
- Amount: 1 pair



UT-L13 Probes

- Leads length: 1200mm, Rod length: 128mm
- Tip length: 18mm, with ϕ 4mm standard lantern tip
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Temperature condition: -15°C~40°C
- Features and application: Double insulated UL authenticated material, ϕ 4mm standard lantern-tip probe, which can be connected to standard alligator clips and test leads, removable tip shield sleeve, general type probes
- Amount: 1 pair



UT-L16 Probes

- Length: 1200mm, Rod length: 133mm
- Tip length: 18mm
- Safety level: CAT III 1000V 16A
- Safety certificate: EN 61010-031 :2015
- Features and application: Double insulated silicone wire material, through hole type input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair